



MS PLUS WOOD FLOORING ADHESIVE

Concrete Moisture Remediation Warranty Registration

CONDITIONS & REGISTRATION

The following conditions must be met for the MS Plus Concrete Moisture Remediation Ten Year Warranty to be valid:

- a) All Conditions and Exclusions of the MS Plus Wood Flooring Adhesive Installation System Warranty for Concrete Moisture Remediation dated 7/1/09 must be met.
- b) Application of Taylor MS Plus Wood Flooring Adhesive with the Taylor Glide-On trowel must be done in complete accordance with Taylor written instructions.
- c) The flooring installation must be done in accordance with the flooring manufacturer's instructions.

Fill out this form completely and attach copies of product purchase receipts and moisture level test results. This information is required to process warranty claims. Incomplete or partially filled out forms will not be accepted, nor will forms submitted without copies of purchase receipts and test results. Complete form online and attach scanned documentation or mail to: W.F. Taylor Co., Inc., Attn: MS Plus Warranty for Concrete Moisture Remediation Registration, 209 Crown Lake Drive SE, Dalton, GA 30721. We cannot accept faxed receipt copies due to legibility concerns. This form and attachments **must be submitted within 30 days** of the completion of the installation. Please type or print clearly.

REGISTRANT

Name: _____
 Company: _____
 Address: _____
 City, State, Zip: _____
 Phone: _____

WHERE TAYLOR PRODUCTS PURCHASED

Company: _____
 Address _____
 City, State, Zip: _____
 Phone: _____

INSTALLATION SITE INFORMATION

Installer Name: _____
 Address: _____
 City, State, Zip: _____

Phone: _____
 Date of Installation: _____
 Size of Job (SF): _____

Type of Flooring Installed: _____

MS Plus Adhesive:

Batch # (s) _____

Gallons Used: _____

Trowel Used: _____

Concrete Condition:

New (how old?) _____ or Existing (how old?) _____

Porous or Non-Porous Sanded Diamond Ground

Substrate Preparation (brief description): _____



MS PLUS WOOD FLOORING ADHESIVE

Concrete Moisture Remediation Warranty Registration

Test Results and Conditions Prior to Application of Adhesive:

Number of Calcium Chloride Tests Run: _____ Number of Relative Humidity Readings Taken: _____

Highest Moisture lbs./RH% Level: _____ Interior Temp. & Humidity _____

Exterior Conditions (dry, wet, cold, hot, etc.) _____

Summary of Completed Installation: _____

- I certify that all Taylor MS Plus Pre-Installation & Installation Instructions were strictly adhered to and all steps were completely followed.
- I certify that all Conditions and Exclusions as stated in the *Taylor MS Plus Wood Flooring Adhesive Installation System Warranty for Concrete Moisture Remediation Effective July 1 2009* were strictly adhered to, without exception.
- I certify that all information provided on this registration form is accurate, and documentation is available.

Printed Name

Date

Signature

W.F. Taylor Co., Inc.

Corporate Office
11545 Pacific Avenue
Fontana, CA 92337
800-397-4583

Eastern Regional Office
209 Crown Lake Drive SE
Dalton, GA 30721
800-868-4583