



**DESCRIPTION: 2060 MULTI-PURPOSE ADHESIVE:** Taylor 2060 is a latex-based economy grade floorcovering adhesive developed for the indoor installation of many types of carpets and sheet goods designed for direct glue down, excluding those with vinyl backings. Taylor 2060 is freeze/thaw stable, easy to spread, and has ample open time, with strong wet tack and a permanent water resistant bond.

**USE TO INSTALL: Carpet:** most carpet backings such as jute backed, polypropylene backed (Action Bac), needle punched, rubber backed. **Sheetgoods:** felt backed sheet vinyl. **NOT** recommended for vinyl backed carpet or vinyl backed sheets goods.

**USE OVER:** Use over association grade particle board underlayment, association grade plywood underlayment and porous concrete (above, on and below grade) in the absence of excessive moisture, alkali and hydrostatic pressure. Not recommended over existing vinyl flooring. Do not use outdoors.

**SUBSTRATE PREPARATION:** Substrate must be clean, level, and dry. Remove all foreign substances such as wax, grease, dirt, curing compounds and any substance or chemical that would interfere with a good bond. Fill all cracks, holes and low spots with a latex fortified Portland cement based patching compound. Sand high spots, install approved underlayment over tongue and groove flooring to eliminate the possibility of telegraphing. Concrete floors must be dry and free of hydrostatic pressure when using on or below grade. The pH level of concrete must be between 5 and 9 (do not install if over 9) and moisture level of concrete must be below 5 lbs./1000 sq. ft./24 hours using an anhydrous calcium chloride test kit according to ASTM F-1869 test method. Relative Humidity readings according to ASTM F-2170 should not exceed (RH) 75%. If both tests are performed the RH test is the qualifying standard.

**TROWEL RECOMMENDATIONS**

Flooring Product	Trowel Size* and Notch	Coverage
Sheet goods	1/16" x 1/16" x 1/16" Square-Notch 1.6mm x 1.6 mm x 1.6mm	Up to 250 sq. ft./gal Up to 6.1 sq. meters/liter
Smooth backed carpet	1/8" x 1/8" x 1/16" V-Notch 3.2 mm x 3.2 mm x 1.6 mm	Up to 110 sq. ft./gal Up to 2.7 sq. meters/liter
Rough back and ribbed carpet	1/8" x 1/8" x 1/16" U-Notch 3.2 mm x 3.2 mm x 1.6 mm	Up to 72 sq. ft./gal Up to 1.8 sq. meters/liter

\*Trowel dimensions are width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and the angle at which the trowel is held.

**INSTALLATION:** For best results, the room, floorcovering and adhesive should be between 65°F (18°C) and 95°F (43.09°C) for 24 hours before, during, and after the installation. Relative humidity should be between 30% and 60%. Use the trowel recommended for the type of installation. W.F. Taylor cannot know all job conditions, therefore, it is the user's responsibility to use an adequate amount of adhesive for the job condition.

**Carpet:** The carpet should be installed in most cases within 30 minutes after the adhesive application. The tacky method of installation allows the adhesive to dry to a tacky state. Work out all bubbles or ripples with a push broom or carpet tube. Approximately 30 minutes after the installation, the carpet should be rolled with a 35 lb. (15.88 kg) carpet roller. Do not use a heavy linoleum roller.

**Sheet Goods:** Sheet goods should be installed within 20 minutes after the application of the adhesive. After installation, the floor should be rolled with a 75-100 lb. (34-45.4 kg) linoleum roller.

**PHYSICAL PROPERTIES**

- Base: Synthetic rubber, resin blend
- Appearance: Off-white, medium paste
- Working Time: 20 - 30 minutes under normal conditions
- Shelf Life: One year in unopened container at 70°F (21°C).
- Flammability: Non-flammable, qualified for NFPA Class A and UBC Class 1 fire ratings as determined by the ASTM E-84 Tunnel Test. Conforms to the requirements of the Hill-Burton Act and passes the Pill Test.
- Other Features: Freeze/thaw stable to 10° F. Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
- Clean Up: Use warm soapy water while adhesive is still wet. When dry, use Taylor Touchdown #9 Adhesive Remover/Stripper.

**CAUTION:** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY INFORMATION:** This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For information, call Technical Services at 800-868-4583; visit us on the web at [www.wftaylor.com](http://www.wftaylor.com); or e-mail us at [info@wftaylor.com](mailto:info@wftaylor.com).