



DESCRIPTION: 2090 VINYL BACK FLOORCOVERING ADHESIVE

Taylor 2090 Vinyl Back Floorcovering Adhesive is a fast drying, hard set adhesive for the installation of solid vinyl tile, vinyl backed sheet goods, and vinyl backed carpet over porous floors. Intended for full spread application of vinyl backed sheet goods. Not intended for use on perimeter type installations. It will not contribute to sheet goods discoloration or plasticizer migration.

USE OVER

Underlayment grade hardboard, association grade particle board, exterior grade plywood and moisture-free on, above or below grade concrete in the absence of excessive moisture or hydrostatic pressure. Moisture levels of concrete slabs must be 5 lb. or less per 1000 square feet per 24 hours (2.27 kg /92.9 m² /24 hours) using an anhydrous calcium chloride test according to ASTM F-1869. Relative Humidity readings according to ASTM F-2170 should not exceed (RH) 85%. If both tests are performed the RH test will be the qualifying standard. Test concrete subfloor for alkalinity (pH of floor should be between 5 and 9). Take corrective measures if concrete surface pH is outside these limits.

SUBSTRATE PREPARATION

Substrate must be sound, smooth, clean, level, and dry. It must be free of dust, dirt, grease, oil, paint, incompatible curing compounds or sealers, fire retardant chemicals, release agents, or any other foreign substance that might interfere with a good bond. Substrates must be properly leveled to prevent telegraphing. Fill all cracks, holes and low spots with a polymer modified cementitious patching or leveling compound and allow to fully cure before applying adhesive. High spots must be leveled.

The adhesive, floor covering, and area to receive flooring must be maintained at a temperature of 65° to 95° F (18°- 35° C) and at a relative humidity of 30% to 60% for 72 hours before, during, and after installation. Follow the flooring manufacturer's guidelines regarding site conditions and installation. Open time will vary with fluctuation of temperature and humidity or porosity of the substrate.

INSTRUCTIONS

Spread adhesive with a 1/16" x 1/16" x 1/16" square-notch trowel. Lay tiles or sheet goods into wet adhesive. For permanent installation of 6' PVC backed carpet, use a 3/32" x 3/32" x 3/32" v-notch trowel. Lay carpet into wet adhesive. Adhesive must transfer to form proper bond.

PHYSICAL PROPERTIES

Base:	Sythetic latex blend.
Color:	Off-white.
Consistency:	Smooth, easy-to-spread mastic.
Open Time:	30 minutes.
Shelf Life:	One year in unopened container at 70° F.
Flammability:	Non-flammable, qualified for NFPA Class A and UBC Class 1 fire ratings as determined by the ASTM E-84 Tunnel Test. Conforms to the requirements of the Hill-Burton Act and passes the Pill Test.
Other Features:	Freeze/thaw stable to 10° F. Water resistant when dry and cured. Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Clean Up:	Use warm soapy water while adhesive is still wet. When dry, use Taylor Touchdown #9 Adhesive Remover/Stripper.

CAUTION: DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION: This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.