
DESCRIPTION: TOUCHDOWN® 722 WATER-BASED PAD ADHESIVE

Taylor Touchdown 722 is a specially formulated latex-based adhesive for bonding all types of carpet padding to all types of floors. It exhibits a fast-wet suction and will hold pad in place so that the carpet can be stretched immediately. It is easy to pour, ready to use.

APPLICATION

The surface to which Taylor 722 is to be applied must be clean and dry, and free of excessive alkali. Remove all foreign substances such as wax, grease, dirt and sand. Using spout, apply beads of adhesive about 1/4" wide, 3" to 4" away from each wall and in a crisscross pattern the full length of all pad seams. Using a scrap of pad or carpet, spread the adhesive to form an even film, permit the adhesive to dry for one to two minutes before laying the pad, and walk pad into adhesive at the wall and all seam areas.

PHYSICAL PROPERTIES

Base: Hydrocarbon resin and synthetic latex
Appearance: Beige liquid
Odor: Mild
Shelf Life: One year in unopened container at 70°F.
Coverage: Up to 200 sq. ft. per gallon or approximately 1,000 linear ft. per gallon
Flammability: Non-flammable. Conforms to all current flammability requirements for a Class A flame spread rating.
Other features: Freeze/thaw stable to 10° F (-12.22°C). Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Clean-up: Use soapy water while the adhesive is wet. If dried, use Touchdown #9 Adhesive Remover/Stripper.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

LIMITED WARRANTY

This product is manufactured according to exacting quality control standards and warranted to be free of manufacturing defects. Defective materials called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.