



## IRONWOOD™

### Premium Grade Wood Flooring Adhesive

When it comes to finding an all-around, premium wood flooring adhesive, IRONWOOD™ nails it. Ironwood™ is ideal for all engineered, solid, bamboo, cork and parquet flooring recommended for glue-down installation.

#### FEATURES:

- Moisture protection for most common installations
- Contributes to sound reduction
- High strength water resistant bond
- Easy clean-up
- Health/Environmentally conscious formula design [Non-urethane, isocyanate free]

#### WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
4 gal.	1	48 lbs.	20-70 sq.ft./gal.*

#### MAXIMUM MOISTURE AND PH LEVELS

CaCl <sup>2</sup> Max.	RH Max	pH Range
10 lbs.	90%**	N/A

\*\*Achieve 95% RH coverage when used with Taylor's Zephyr moisture vapor barrier.

#### \* For Moisture Control, Crack Isolation, Sound Reduction, And Wood Adhesion:

For Solid, Engineered, & Bamboo Wood Flooring Greater Than 9/16" Thick For Wide/Long Plank  
Estimated Coverage 20 sq ft/gal



1/2" x 15/32" V-Notch  
(12.7mm x 11.9mm V-Notch)

For Solid, Engineered, & Bamboo Wood Flooring Less Than 9/16" Thick  
Estimated Coverage 30 sq ft/gal



1/4" x 1/4" V-Notch  
(6.35mm x 6.35mm V-Notch)

#### \* For Only Wood Adhesion:

For Dry-Back Wood Parquet Flooring  
Estimated Coverage 60-70 sq ft/gal



1/8" x 1/8" x 1/8" Sq. Notch  
(3.2mm x 3.2mm x 3.2 mm Sq. Notch)

For Solid, Engineered, & Bamboo Wood Flooring  
Estimated Coverage 50-60 sq ft/gal



3/16" x 1/4" x 5/16" V-Notch  
(4.8mm x 6.4mm x 7.9 V-Notch)

Shelf Life: 1 Year

SKU: IRONWOOD-4

Taylor Technical Support  
800-868-4583 x 2221

East Coast Customer Service  
800-868-4583 x 1163

West Coast Customer Service  
800-868-4583 x 1162

For more information visit [www.wftaylor.com](http://www.wftaylor.com)