



### SOUNDLEVEL™

Next Generation Sound Reducing & Self-Leveling Liquid Underlayment

SOUNDLEVEL™ sound reducing liquid & self-leveling underlayment is designed for all floating floor systems [vinyl tile/plank, laminate, and wood] to reduce sound transmission [up to IIC 71 and STC 67]. SOUNDLEVEL™ also controls moisture levels, patches up to 1/8" cracks, levels substrate unevenness, and enhances thermal insulating properties of the floor.

#### FEATURES:

- Quiets floors
- Self-leveling and cures to a sealed flat membrane
- Controls moisture and enhances thermal insulation
- Replaces traditional underlayments
- Designed for compatibility with Taylor adhesives
- Health/Environmentally conscious formula design

#### WEIGHTS AND COVERAGE

| SIZE   | PACK | WEIGHT  | COVERAGE              |
|--------|------|---------|-----------------------|
| 4 gal. | 1    | 52 lbs. | Up to 100 sq.ft./gal. |
| 2 gal. | 1    | 26 lbs. |                       |

#### MAXIMUM MOISTURE AND PH LEVELS

| CaCl <sup>2</sup> Max. | RH Max | pH Range |
|------------------------|--------|----------|
| 10 lbs.                | 90%    | N/A      |

**SKU: SOUNDLEVEL-4**

Taylor Technical Support  
800-868-4583 x 2221

East Coast Customer Service  
800-868-4583 x 1163

West Coast Customer Service  
800-868-4583 x 1162

For more information visit [www.wftaylor.com](http://www.wftaylor.com)

For Sound Reducing & Moderate Moisture Control

1/16" x 3/32" Sawtooth



(1.59mm x 2.4mm Sawtooth)

For Patching & Leveling

3/16" x 5/32" Sawtooth



(4.8mm x 4.0mm Sawtooth)

Shelf Life: 1 Year