

Finale™ [2040]

Premium Wall Base Adhesive

DESCRIPTION

Finale is a white, hard-setting, acrylic adhesive formulated for the installation of rubber and vinyl cove base over wood, concrete, brick, plaster, wallboard or other porous surfaces. Exhibits fast tack and wet suction to hold on inner and outer corners. Will not contribute to staining, shrinkage or plasticizer migration.

Note: Do not apply over non-porous surfaces such as vinyl wall coverings, laminated masonite, or plastic laminates.

SURFACE PREPARATION

Roughen glossy surfaces such as enamel paint and rinse alkaline surfaces with vinegar or acetic acid. The surface must be structurally sound, clean, level, dry, and free from dust, dirt, wax, grease, loose paint, plaster, and other contaminants that may interfere with proper bonding. Fill all holes and cracks with a cement based patching compound and sand high spots.

INSTRUCTIONS

Cove base should be laid out flat, and the room, cove base and adhesive should be 65°F [18.3°F] for 24 hours prior to, during, and after installation. Note: for best adhesion with molded rubber cove base, it is recommended to wipe the back with mineral spirits prior to installation.

1. Spread the adhesive on the back of the cove base with 3/32" x 3/32" x 3/32" [2.4mm x 2.4mm x 2.4mm] V-notch trowel or cartridge gun, to leave an ample amount of adhesive for the wall surface.
2. The cove base can be set in place up to 15 minutes after the adhesive is spread. Press firmly to the wall and rub or roll towards previously installed cove base. This will give a smooth, even bond with no gaps at the seams. Check to see that the adhesive has proper transfer to the wall.

CLEANUP

Use soap and water if adhesive is still wet. If dried, use Taylor Touchdown #9 Adhesive Remover/Stripper

RECOMMENDED TOOLS:

3/32"x3/32"x3/32" V-notch trowel 2.4mm x 2.4mm x 2.4mm	280 linear feet of 4" cove base per gallon
---	--

OTHER PROPERTIES:

Appearance: Off-white, heavy paste

Open Time: Up to 30 minutes

Shelf Life: One year in unopened container at 70 degrees F.

Coverage: Up to 280 linear feet of 4" cove base per gallon.

Other Features: Freeze-thaw stable to 10°F.

STORAGE

This product should be stored at temperatures between 50° and 90° F [15°- 32° C]. Storage conditions outside this range may cause product viscosity to increase.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting.

Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583 ext 2221, visit us on the web at www.wftaylor.com or e-mail us at tech@wftaylor.com.

This product is packaged with 100% post-industrial reground plastic.

© W. F. Taylor, LLC Dalton GA. All Rights Reserved. Visit wftaylor.com

Technical Service 800.868.4583 Ext: 221 or e-mail us at tech@wftaylor.com

Customer Service 866.818.7434