

2090

Vinyl Back Floor Covering Adhesive

DESCRIPTION

Taylor 2090 Vinyl Back Floorcovering Adhesive is a fast drying, hard set adhesive for the installation of solid vinyl tile, vinyl backed sheet goods, and vinyl backed carpet over porous floors. Intended for full spread application of vinyl backed sheet goods. Not intended for use on perimeter type installations. It will not contribute to sheet goods discoloration or plasticizer migration.

APPROVED SUBSTRATES

Underlayment grade hardboard, association grade particle board, exterior grade plywood and moisture-free on, above or below grade concrete in the absence of excessive moisture or hydrostatic pressure. Moisture levels of concrete slabs must be 5 lb. or less per 1000 square feet per 24 hours (2.27 kg /92.9 m² /24 hours) using an anhydrous calcium chloride test according to ASTM F-1869. Relative Humidity readings according to ASTM F-2170 should not exceed [RH] 85%. If both tests are performed the RH test will be the qualifying standard. Test concrete subfloor for alkalinity [pH of floor should be between 5 and 9]. Take corrective measures if concrete surface pH is outside these limits.

SUBSTRATE PREPARATION

Substrate must be sound, smooth, clean, level, and dry. It must be free of dust, dirt, grease, oil, paint, incompatible curing compounds or sealers, fire retardant chemicals, release agents, or any other foreign substance that might interfere with a good bond. Substrates must be properly leveled to prevent telegraphing. Fill all cracks, holes and low spots with a polymer modified cementitious patching or leveling compound and allow to fully cure before applying adhesive. High spots must be leveled.

The adhesive, floor covering, and area to receive flooring must be maintained at a temperature of 65° to 95° F [18°- 35° C] and at a relative humidity of 30% to 60% for 72 hours before, during, and after installation. Follow the flooring manufacturer's guidelines regarding site conditions and installation. Open time will vary with fluctuation of temperature and humidity or porosity of the substrate.

INSTRUCTIONS

Spread adhesive with a 1/16" x 1/16" x 1/16" square-notch trowel. Lay tiles or sheet goods into wet adhesive. For permanent installation of 6' PVC backed carpet, use a 3/32" x 3/32" x 3/32" v-notch trowel. Lay carpet into wet adhesive. Adhesive must transfer to form proper bond.

CLEANUP

Use warm soapy water while adhesive is still wet. When dry, use Taylor Touchdown #9 Adhesive Remover/Stripper.

RECOMMENDED TOOLS

Type of Installation	Trowel Size* and Notch	Coverage
Vinyl Tile & Plank Vinyl Backed Sheet Goods	1/16" X 1/16" X 1/16" Square Notch [1.6mm X 1.6mm X 1.6mm]	Up to 250 ft ² per gallon
Vinyl Backed Carpet	3/32" X 3/32" X 3/32" V-Notch [2.4mm X 2.4mm X 2.4mm]	Up to 160 ft ² per gallon

*Trowel dimensions are width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and the angle at which the trowel is held.

**IT IS THE INSTALLER'S RESPONSIBILITY TO APPLY THE PROPER AMOUNT OF ADHESIVE FOR THE JOB CONDITION.

OTHER PROPERTIES:

Appearance: Off-white.

Open time: 30 minutes

Shelf life: One year in unopened container at 70° F.

STORAGE

Freeze/thaw stable to 10° F.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting.

Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583 ext 2221, visit us on the web at www.wftaylor.com or e-mail us at tech@wftaylor.com.

© W. F. Taylor, LLC Dalton GA. All Rights Reserved. Visit wftaylor.com

Technical Service 800.868.4583 Ext: 221 or e-mail us at tech@wftaylor.com

Customer Service 866.818.7434