

# 705 Edge-Lock

Edge Sealing Adhesive

## **DESCRIPTION**

Edge Lock is a fast-drying latex seam sealer recommended for seaming non-vinyl back carpets and all types of cushion-back carpet. It can also be used to seal cut edges of carpet to prevent raveling. Available in quart container.

### **INSTRUCTIONS**

Ready for use, no stirring required.

This product is for refill use only: Remove cap and fill an 8oz. bottle with Edge Lock adhesive. Replace cap when done. Edge Lock should only be applied to the edges of the carpet backing. Avoid contact with the nap of the carpet and avoid over application of the sealer to the carpet edge.

DO NOT expose to heavy traffic for 24 hours.

DO NOT expose to water for at least 4 days.

DO NOT expose to standing water.

#### **CLEANUP**

While wet, use water. Clean up spills immediately. Avoid letting Edge Lock dry on the face of carpets. Dried Edge Lock can be removed with Touchdown #9 Clean-up Solvent.

## **RECOMMENDED TOOLS**

Type of Installation	Application Tool	Coverage
Seam Sealer	Brush or carpet scrap	Approximately 75 linear feet
		per 8 oz. container

<sup>\*</sup> Coverage is approximate and may vary depending on porosity of substrate and the angle at which the trowel is held.

#### OTHER PROPERTIES:

Appearance: White, dries clear

Shelf life: Six months in unopened container

#### **CAUTION**

Do not take internally. If swallowed, do not induce vomiting. Call a physician. KEEP OUT OF THE REACH OF CHILDREN. Keep away from open flames. Edge-Lock is water based but contains small amount of Isopropyl alcohol which could accumulate in an open space during storage.

## WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583 ext 2221, visit us on the web at www.wftaylor.com or e-mail us at tech@wftaylor.com.

<sup>\*\*</sup>IT IS THE INSTALLER'S RESPONSIBILITY TO APPLY THE PROPER AMOUNT OF ADHESIVE FOR THE JOB CONDITION.