



STEADFAST™

Premium, Fast Drying, VCT Adhesive

STEADFAST™ is an advanced, cross-linking, resin blend pressure sensitive adhesive recommended for the interior installation of vinyl composition tile (VCT) and closed-cell foam-back hardwood parquet over approved substrates. DO NOT use to install solid vinyl backed flooring. The cross-linking technology is formulated to dry fast and gradually build into a tenacious waterproof bond when fully cured. SteadFast is a solvent-free, low-odor adhesive that meets all federal, state and local government indoor air quality regulations.

FEATURES:

- High Tack/High Grab/Extended Working Time
- Greater Flexibility for Large Installations
- High Strength, Water-Proof Bond When Cured
- Health/Environmentally Conscious Formula Design

WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
1 gal.	4	35 lbs.	up to 250 sq.ft./gal.
4 gal.	1	35 lbs.	

MAXIMUM MOISTURE AND PH LEVELS

CaCl ² Max.	RH Max	pH Range
8 lbs.	90%	Up to 9

SKU: STEADFAST-4; STEADFAST-1

Taylor Technical Support
800-868-4583 x 2221


East Coast Customer Service
800-868-4583 x 1163

West Coast Customer Service
800-868-4583 x 1162

For more information visit www.wftaylor.com

VCT over porous
Up to 350 sq. ft./gal

1/16" x 1/32" x 1/32" U notch



(1.6mm x 0.8mm x 0.8mm U notch)

VCT over non-porous
Up to 400 sq. ft./gal

1/16" x 1/32" x 5/64" U notch



(1.6mm x 0.8mm x 2.0mm U notch)

Foam back parquet
Up to 250 sq. ft./gal

1/16" x 1/16" x 1/16" Sq. notch



(1.6mm x 1.6mm x 1.6mm Sq. notch)

Shelf Life: 1 Year