



RIDGELINE™

Next Generation Wood Flooring Adhesive & Moisture Control System

RIDGELINE™ is a Next Generation adhesive formulated for use in the installation of all engineered, solid, bamboo, cork and parquet flooring recommended for glue-down installation. RIDGELINE™ effectively reduces moisture vapor transmission from concrete subfloors, protecting wood flooring from damage.

FEATURES:

- Extreme moisture protection.
- Excellent bond strength on all wood flooring products including wide/long plank styles.
- Quick and easy installation and clean up.
- Quiets floors.
- Health/Environmentally conscious formula design [non-urethane & isocyanate free]

WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
4 gal.	1	45 lbs.	20-70 sq.ft./gal.*

MAXIMUM MOISTURE AND PH LEVELS

CaCl ² Max.	RH Max	pH Range
No Test Req.	No Test Req.	Up to 14

* For Moisture Control, Crack Isolation, Sound Reduction, And Wood Adhesion:

For Solid, Engineered, & Bamboo Wood Flooring Greater Than 9/16" Thick For Wide/Long Plank
Estimated Coverage 20 sq ft/gal



1/2" x 15/32" V-Notch
(12.7mm x 11.9mm V-Notch)

For Solid, Engineered, & Bamboo Wood Flooring Less Than 9/16" Thick
Estimated Coverage 30 sq ft/gal



1/4" x 1/4" V-Notch
(6.35mm x 6.35mm V-Notch)

* For Only Wood Adhesion:

For Dry-Back Wood Parquet Flooring
Estimated Coverage 60-70 sq ft/gal



1/8" x 1/8" x 1/8" Sq. Notch
(3.2mm x 3.2mm x 3.2 mm Sq. Notch)

For Solid, Engineered, & Bamboo Wood Flooring
Estimated Coverage 50-60 sq ft/gal



3/16" x 1/4" x 5/16" V-Notch
(4.8mm x 6.4mm x 7.9 V-Notch)

Shelf Life: 1 Year

SKU: RIDGELINE-4

Taylor Technical Support
800-868-4583 x 2221

East Coast Customer Service
800-868-4583 x 1163

West Coast Customer Service
800-868-4583 x 1162

For more information visit www.wftaylor.com