



SOUNDLEVEL™

Next Generation Sound Reducing & Self-Leveling Liquid Underlayment

SOUNDLEVEL™ sound reducing liquid & self-leveling underlayment is designed for all floating floor systems [vinyl tile/plank, laminate, and wood] to reduce sound transmission [up to IIC 71 and STC 67]. SOUNDLEVEL™ also controls moisture levels, patches up to 1/8" cracks, levels substrate unevenness, and enhances thermal insulating properties of the floor.

FEATURES:

- Quiets floors
- Self-leveling and cures to a sealed flat membrane
- Controls moisture and enhances thermal insulation
- Replaces traditional underlayments
- Designed for compatibility with Taylor adhesives
- Health/Environmentally conscious formula design

WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
4 gal.	1	52 lbs.	Up to 100 sq.ft./gal.
2 gal.	1	26 lbs.	

MAXIMUM MOISTURE AND PH LEVELS

CaCl ² Max.	RH Max	pH Range
10 lbs.	90%	Up to 14

For Sound Reducing & Moderate Moisture Control

1/16" x 3/32" Sawtooth



(1.59mm x 2.4mm Sawtooth)

For Patching & Leveling

3/16" x 5/32" Sawtooth



(4.8mm x 4.0mm Sawtooth)

Shelf Life: 1 Year

SKU: SOUNDLEVEL-4

Taylor Technical Support
800-868-4583 x 2221

East Coast Customer Service
800-868-4583 x 1163

West Coast Customer Service
800-868-4583 x 1162

For more information visit www.wftaylor.com