



## 2098

Transitional Pressure Sensitive® Adhesive For LVP/LVT, Fiberglass & Vinyl Sheet, VCT and Carpet Tile

2098 is an industry-leading Transitional Pressure Sensitive® Adhesive with ColorReady™ technology designed to meet the need for a multi-functional flooring adhesive. This solvent-free, easy troweling product provides greater flexibility for installations using multiple flooring materials. It can be used to install luxury vinyl tile (LVT), luxury vinyl plank (LVP), carpet tile, fiberglass backed sheet and sheet vinyl flooring. ColorReady™ technology helps to easily identify when to install your flooring.

### FEATURES:

- ColorReady™
- High tack / fast grab / extended working time
- Greater flexibility for large installations
- High strength, water resistant bond
- Health/Environmentally conscious formula design

### WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
4 gal.	1	34 lbs.	Up to 350 sq.ft./gal.
1 gal.	4	36 lbs.	

### MAXIMUM MOISTURE AND PH LEVELS

CaCl <sub>2</sub> Max.	RH Max	pH Range
10 lbs.	97%	5 to 9

Over porous substrates  
[LVT/LVP, Sheet Vinyl]  
Up to 180 sq ft/ gal

1/16" x 1/16" x 1/16" Sq. notch



(1.6mm x 1.6mm x 1.6mm Sq. notch)

Over non-porous substrates  
[LVT/LVP, Sheet Vinyl]  
Up to 260 sq ft/gal

1/16" x 1/32" x 1/32" U notch



(1.6mm x 0.8mm x 0.8mm U notch)

Carpet Tile and Fiberglass  
Sheet Goods  
Up to 350 sq ft/ gal



3/8" (10 mm)  
short nap paint roller

Shelf Life: 2 Years

**SKU: 2098-4, 2098-1**

Taylor Technical Support  
800-868-4583 x 2221

East Coast Customer Service  
800-868-4583 x 1163

West Coast Customer Service  
800-868-4583 x 1162

For more information visit [www.wftaylor.com](http://www.wftaylor.com)