



### PINNACLE™ [TAYLOR 2091]

Premium Transitional Pressure Sensitive® Adhesive For LVP/LVT

PINNACLE™ can be used with LVT/LVP, solid vinyl sheet, rubber tile/sheet and vinyl & rubber stair treads. This solvent-free, easy troweling product provides excellent installations for tile-over-tile applications.

#### FEATURES:

- High-strength, water resistant bond for demanding installations
- High tack / fast grab
- Quick setting
- Health/Environmentally conscious formula design

#### WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
1 gal.	4	36 lbs.	Up to 250 sq.ft./gal.
4 gal.	1	34 lbs.	

#### MAXIMUM MOISTURE AND PH LEVELS

CaCl <sup>2</sup> Max.	RH Max	pH Range
12 lbs.	99%	Up to 12

Over porous substrates  
(Vinyl Tile & Plank, Rubber Tile, Vinyl & Rubber Stair Treads)

1/16" x 1/16" x 1/16" Sq. notch



(1.6mm x 1.6mm x 1.6mm Sq. notch)

Over porous substrates  
(Solid Vinyl Sheet Goods, Rubber Sheet Goods)

1/16" x 1/32" x 1/32" U notch



(1.6mm x 0.8mm x 0.8mm U notch)

Over non-porous substrates  
(Vinyl Tile & Plank, Rubber Tile, Vinyl & Rubber Stair Treads)

1/16" x 1/32" x 5/64" U notch



(1.6mm x 0.8mm x 2.0mm U notch)

Shelf Life: 2 Years

**SKU: PINNACLE-4, PINNACLE-1**

Taylor Technical Support  
800-868-4583 x 2221

East Coast Customer Service  
800-868-4583 x 1163

West Coast Customer Service  
800-868-4583 x 1162

For more information visit [www.wftaylor.com](http://www.wftaylor.com)