



RESOLUTE™ [MS+RESILIENT]

Premium Multi-Function Adhesive for Resilient Flooring

RESOLUTE™ is formulated for the installation of all types of resilient flooring. This solvent free, easy troweling, high strength product is an excellent replacement for epoxy and urethane adhesives, and provides excellent installations for vinyl, rubber, fiberglass & polyolefin backed flooring, approved recycled resilient flooring, tile, plank, and sheet goods over both porous and non-porous surfaces.

FEATURES:

- Replaces Urethane & 2 Part Epoxy products
- Moisture protection for most common installations
- Contributes to sound reduction, thermal insulation and crack isolation
- LEED v4 contributing [CDPH v1.2]

WEIGHTS AND COVERAGE

SIZE	PACK	WEIGHT	COVERAGE
2 gal.	1	27 lbs.	Up to 250 sq.ft./gal.

MAXIMUM MOISTURE AND PH LEVELS

CaCl ₂ Max.	RH Max	pH Range
12 lbs.	99%	No test req.

For Sheet Goods & Moisture Barrier Application


1/16" x 1/16" x 1/16" Sq. notch



(1.6mm x 1.6mm x 1.6mm Sq. notch)

For Tile & Plank

1/16" x 1/32" x 1/32" U notch



(1.6mm x 0.8mm x 0.8mm U notch)

Shelf Life: 1 Year

SKU: RESOLUTE-2

Taylor Technical Support
800-868-4583 x 2221

East Coast Customer Service
800-868-4583 x 1163

West Coast Customer Service
800-868-4583 x 1162

For more information visit www.wftaylor.com